# Soft

2 m | Heavy Traffic | PUR Coating






8003




8101



8001



8002



8602



8220

# Medinpro

Indoor Air Quality | Heavy Traffic | Anti-bacterial | 100% Recyclable

Medinpro is a durable, multi-purpose homogeneous vinyl flooring with non-directional designs. It is an ideal solution for heavy traffic areas such as healthcare, education, offices, retail and public buildings. MEDI-Pro has a surface treated with PUR reinforcement, which means no wax and no polish for life and excellent life cycles costs. The PUR also provides a good base for future maintenance procedures.

## INSTALLATION

Medinpro homogenous vinyl should be stored vertically. Installation should be made in accordance with installation guidelines supplied and regularly updated by our technical department. Installation should be carried out in accordance with local standards. Subfloor to be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate an effective Damp Proof Membrane. The material must be allowed to acclimatise 24 hours prior to installation in a room temperature of between 18-24°C. All seams must be heat welded using the matching weld rod.

## MAINTENANCE

Maintenance should be carried out regularly to retain the appearance and durability of the floor. The floorcovering should be maintained with regular sweeping and damp mopping using a neutral cleanser, or machine scrubbing with an appropriate pad. Further maintenance

| DESCRIPTION | | | Medinpro |
|---|---|---|---|
| Total thickness | EN 428 | mm | 2.0mm |
| Wearlayer thickness | EN 429 | mm | 2.0mm |
| Roll width | EN 426 | cm | 200cm |
| Roll length | EN 426 | m | 20m |
| **CLASSIFICATION** | | | |
| Classification | EN 685 | class | 34-43 |
| Fire rating | EN 13 501-1 | -- | Class Bfl-S1 |
| | GB 8624-2006 | -- | GB 8624 B1 |
| Toxic testing | GB 18586-2001 | -- | Pass |
| Electrical resistance | EN 1815 | kv | < 2 |
| | EN 1081 | Ω | ≥109 |
| Slip resistance dry | EN 13893 | -- | ≥0.3 |
| Slip resistance wet | DIN 51130 | class | R9 |
| **PERFORMANCE** | | | |
| Dimensional stability | EN 434 | % | ≤0.40 |
| Residual indentation | EN 433 | mm | 0.03 |
| Thermal conductivity | EN 12 524 | W/(m.K) | 0.25 |
| Colour fastness | EN ISO 105 - B02 | degree | ≥6 |
| Chemical resistance | EN 423 | -- | Good |
| Castor wheel test | EN 425 | -- | Suitable |
| Impact sound reduction | EN ISO 717/2 | dB | Approx.+4 |
| Flexibility | EN 435 | -- | Excellent |
| Anti-bacterial and fungicidal | MRSA | -- | Good |
| | DIN EN ISO 846 -A/C | -- | Good |
| Surface treatment | | | PUR |
| Underfloor heating | | °C | Suitable max.28 |
| **CE MARKING** CE | EN 14041 | | |

**Produced by Interio**
**Made in Belgium**

INTERIO FLOOR SOLUTIONS

Homogeneous Vinyl

Medinpro



# Medinpro

Homogeneous Vinyl

> Healthcare
> Education
> Offices
> Retail
> Public Building

ID FLOORING
FLOORS THAT DEFINE YOU

# Flex

2 m | Heavy Traffic | PUR Coating






5310



5305



5324



5312



5329




5340



5306



5366



5320

# Safe

2 m | Heavy Traffic | PUR Coating






6657




6009




6016




6007



6005



6004



6220



6021



6022

# Style

2 m | Heavy Traffic | PUR Coating






7908



7909



7910



7977



7916



7920



7919



7904



7955



7933



7911